

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 018 329 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:  
12.07.2000 Bulletin 2000/28

(51) Int. Cl.<sup>7</sup>: A61H 23/04

(21) Application number: 99125665.2

(22) Date of filing: 22.12.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventors:  
• Ishibashi, Shigemitsu  
2-9-4-Nakaikagami Oota-Ku, Tokyo (JP)  
• Nakao, Haruki  
2-9-4, Nakaikagami, Oota-ku, Tokyo (JP)

(30) Priority: 28.12.1998 JP 37404798

(71) Applicant: Nitto Kohki Co., Ltd.  
Tokyo (JP)

(74) Representative:  
Schurack, Eduard F. et al  
Hofstetter, Schurack & Skora  
Balanstrasse 57  
81541 München (DE)

(54) Air massage system

(57) A compact air massage system which includes massage bodies (10) having a plurality of air-tight chambers (11), a compressed air supply source (6,7) supplying compressed air to the massage body, and a compressed air distribution apparatus arranged between the compressed air supply source and the massage body and having a plurality of switching valves (2) each allowing the respective air-tight chambers to communicate with one of the compressed air supply source and an outer atmosphere. The system further

includes a controller (8) controlling the respective switching valves to allow the respective chambers to be expanded or contracted and check valves (4) each arranged between the compressed air supply source (6,7) and the switching valve (2) and openable from the compressed air supply source toward the direction of the switching valve, by which it is possible to individually adjust pressure in the respective chambers.




FIG. 3

BEST AVAILABLE COPY

EP 1 018 329 A2

## Description

[0001] The present invention relates to an air massage system and, in particular, to an air massage system for massaging a human body by selectively supplying compressed air to a plurality of air-tight chambers provided at massage bodies and selectively discharging the compressed air from these chambers.

[0002] An air massage apparatus of a type set out below is conventionally known which, in order to restore, maintain, improve the human health, performs a continuous massage by sequentially supplying and discharging compressed air to and from a plurality of air-tight chambers of massage bodies worn around the upper or lower limbs of the user.

[0003] Normally, such massage apparatuses include a compressed air distribution apparatus for distributing compressed air from the compressed air supply source to respective air-tight chambers and discharging it from the chambers. For example, the compressed air distribution apparatus is such that respective air-tight chambers are repeatedly expanded and contracted by distributively supplying and discharging the compressed air with the use of ordinary electromagnetic valves.

[0004] The assignee of the present invention has proposed a distribution apparatus in JPN PAT APPLN NO. 9-188967 (filed on July 1st, 1997 and published on January 26th, 1999) in which distribution valve is provided at a supply passageway (header) of a compressed air supply source to correspond to respective air-tight chambers of the massage body. The distribution valve is provided with three-way valves each having a supply port, distribution port and discharge port and being adapted to be opened and closed by a spherical valve body operated by a solenoid section.

[0005] The air massage apparatus, however, requires to use an electromagnetic valve of a small pressure loss which is suited to a pump of a low pressure and high flow rate. In such air massage apparatus, such ordinary electromagnetic valve is larger in size, higher in cost and lower in mass-productivity. Further, this type of electromagnetic valve can adjust a cycle of suction into the air-tight chambers of the massage body, but it cannot adjust the rate of air flow into the respective chamber (see JPN PAT KOKOKU PUBLICATION NO. 51-41794).

[0006] The distribution valve as described in the above-mentioned JPN PAT APPLN NO. 9-188967 can be manufactured at low costs and can supply/discharge a large quantity of compressed air. By doing so it is possible to switch the air-tight chambers selectively or in a predetermined cycle or to effectively supply and discharge air to and from the chambers. However, it is not possible to adjust pressure in the respective chamber.

[0007] In particular, the wearer receives a different feeling when being massaged on the upper or lower limbs. In the case where the pressure in the respective

chambers is the same, it gives pain to the thigh but it is not satisfactory to the top of the foot. The inventor at the present application enables the user to receive a well-balanced body feeling by increasing pressure in the respective chambers toward his or her foot's top or hand's tip.

[0008] The present invention has been achieved based on the above circumstances and it is the object of the present invention to provide an air massage system which is simple in structure and inexpensive and give the user a comfortable message feeling.

[0009] According to the present invention there is provided an air massage system comprising a massage body having a plurality of air-tight chambers, a compressed air supply source for supplying compressed air to the massage body, a compressed air distribution apparatus arranged between the compressed air supply source and the massage body and having a plurality of switching valves allowing the respective chamber to communicate with one of the compressed air supply source and an outer atmosphere, a controller for controlling the respective switching valve to expand or contract the respective chambers and check valves respectively arranged between the compressed air supply source and the respective switching valve and being open in a direction from the compressed air supply source toward a direction of the switching valve, the chambers being individually controllable in pressure.

[0010] By doing so, the user receives a mutually different pressing force at each body part contacting with the respective chamber without simply receiving a uniform pressing force at the respective body part. And the user can receive a well-balanced feeling corresponding to the respective body parts. This provides added massaging effect to the user.

[0011] It is preferable that the compressed air supply source have a tank holding compressed air therein and the controller have a sensor detecting a variation of pressure in the tank and that, by doing so, an output of the compressed air supply source be controlled in accordance with a magnitude corresponding to the pressure in the tank. In this case, there occurs no greater variation in an output of the compressed air supply source and the user never receives any unpleasant feeling resulting from a sudden variation of sound.

[0012] It is also preferable that the controller sequentially supply compressed air to each air-tight chamber in a given supply sequence while adjusting it to an equal or lower level.

[0013] It may be possible to have a shut-off valve interruptible between the tank and the respective check valve and control this shut-off valve by a controller. In this case, it is possible to control the pressure in the respective chamber to any given level.

[0014] It is desirable that the controller store a plurality of control patterns each operating respective switching valves so that the user can select any one of them.

[0015] It is preferable that the switching valve include a valve box having a supply port communicating with the compressed air supply source, a distribution port communicating with the chamber and an discharge port communicating with an outer atmosphere, a valve body movably received in the valve box and allowing the distribution port to communicate with one of both the supply port and the discharge port, a solenoid controlled by the controller, and a movable member coupled to the valve body and driven by the solenoid. In this case, the switching valve is formed as a very compact and simpler structure.

[0016] The valve box has a substantially cylindrical configuration and has a valve seat with the supply port opened on a one-end side of an axial direction thereof and can hold the check valve on an other-end side.

[0017] This summary of the invention does not necessarily describe all necessary features so that the invention may also be a sub-combination of these described features.

[0018] The invention can be more fully understood from the following detailed description when taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a plan view, partly cut away, showing a compressed air distribution apparatus used in an air massage system according to an embodiment of the present invention;

FIG. 2 is a cross-sectional view showing a switching valve of the compressed air distribution apparatus shown in FIG. 1;

FIG. 3 is a circuit diagram schematically showing a pneumatic circuit and electric circuit in the air massage system according to the embodiment of the present invention;

FIG. 4 is a circuit diagram schematically showing another embodiment of the present invention;

FIG. 5 is an explanatory view showing a compressed air supply pattern;

FIG. 6 is an explanatory view showing another compressed air supply pattern;

FIG. 7 is an explanatory view showing the controlling of a pressure adjusting mechanism;

FIG. 8 is an explanatory view showing a pressure difference between a pressure sensor's level and a set pressure level; and

FIG. 9 is an explanatory view showing a whole structure of the air massage system of the present invention.

[0019] With reference to the accompanying drawing, an explanation will be made below about preferred embodiments of the present invention.

[0020] FIGS. 1 to 3 show a compressed air distribution apparatus used for an air massage system adapted to supply compressed air to air chambers of a massage body as will be set out below and discharge the compressed air from the air-tight chambers. This com-

pressed air distribution apparatus comprises a header 1 connected to a compressed air supply source 6, such as an air compressor C, a plurality of switching valves 2 arranged along the header 1 in a parallel way, electromagnetic drive sections 3 each driving a spherical valve body 22 provided in the respective switching valve 2, and check valves 4 each provided between the header 1 and a supply port of the switching valve 2. It is to be noted that the number of the switching valves 2 and that of the checking valves 4 are decided in accordance with the number of compressed air supply passageways and, in the illustrated embodiment, the switching valves 2 and check valves 4 are, respectively, four in number.

[0021] The respective switching valve 2 comprises a substantially cylindrical valve box 21 integrally formed with the header 1 made of a resin, a valve body 22 spherically formed from an elastic material such as silicone rubber, chloroprene rubber, ethylenepropylene rubber or the like, and held at one end side of the valve box 21, and a plate-like cover member 23. The plate-like cover member is joined to the four valve boxes 21 by welding or bonding.

[0022] In the valve box 21, a distribution port 21b is formed to properly communicate with the air-tight chamber 11 provided in the massage body 10 and a conical or spherical valve seat 21c is formed at a circumferential edge portion of a supply port 21a to allow the valve body 22 to abut thereagainst. On the cover member 23 mounted at the openings opposing to the supply ports 21a, valve seats 23a project at intervals equal to the openings of those parallel valve boxes 21 and in number equal to the valve box 21. A discharge port 23b is formed in the respective valve seat 23a and a conical or spherical valve seat 23c is formed in the circumferential edge portion of the discharge port 23b. Further, one end of an operation shaft 31 of an electromagnetic drive section 3 is previously mounted on the valve body 22. The valve body 22 is arranged within the valve box 21 and the cover member 23 is provided at the openings of the valve boxes 21. The other end portion of the operation shaft 31 is projected through the discharge port 23b in the cover member 23 and coupled to the electromagnetic drive section 3. In this connection it is to be noted that only the outer peripheral portion of the valve body 22 may be made of an elastic material.

[0023] Further, on the other-end side of the valve box 21, the check valve 4 is provided to allow a flow of a fluid from the header 1 toward the supply port 21a and to prevent a reverse flow.

[0024] The electromagnetic drive section 3 comprises the operation shaft 31 mounted on the valve body 22, a movable section 32 coupled to the end of the operation shaft 31 projected through the discharge port 23b of the respective switching valve 2, an electromagnet casing 33 containing the movable section 32 and coil, a flange section 34 mounted on the distal end of the movable section 32, a fixing pin 35 connecting both of the operation shaft 31 and flange section 34 to the distal

end portion of the movable section 32, and a spring 36 interposed between the flange section 34 and the electromagnet casing 33.

[0025] When the coil of the electromagnetic drive section 3 is not energized, the movable section 32 is moved, as shown, toward the switching valve 2 side under an urging force of the spring 36, the valve body 22 which is mounted on the distal end of the operation shaft 31 coupled to the movable section 32 abuts the valve seat 21c at the supply port 21a to block the supply port 21a and allow communication between the distribution port 21b and the discharge port 23b. Where, on the other hand, the coil of the electromagnetic drive section 3 is energized, an electromagnetic force is generated, thus retracting the movable section 32 into the electromagnet casing 33 against the urging force of the spring 36. By doing so, the valve body 22 mounted on the distal end of the operation shaft 31 coupled to the movable section 32 is moved away from the valve seat 21c of the supply port 21a into abutting engagement with the valve seat 23c of the discharge port 23b to block the discharge port 23b and allow communication between the supply port 21a and the distribution port 21b.

[0026] The check valve 4 is made of an elastic material and has a beak-like configuration, on one end, with an outlet port 4a at its distal end and a cylindrical configuration, on the other end, with an annular projection 4b axially projected at its outer periphery. The check valve 4 is inserted through an opening 1b of the header 1 and the projection 4b is fitted into an annular groove 1a provided at a circumferential periphery of the supply port 21a communicating with the header 1 integrally extending from the valve box 21. Then the check valve 4 is secured by a retaining ring 4a with a washer 4c interposed therebetween. The respective opening 1b is closed with an integrally formed common cap 44 with a sealing member 43 being interposed between the cap 44 and the outer periphery of the header 1 near the opening 1b.

[0027] The compressed air from the compressed air supply source 6 is supplied past the outlet port 4a of the check valve 4 into the supply port 21a and past the opened distribution port 21b of the switching valve 2 into the air chambers 11 of the massage body 10. During the supply period, the compressed air is never flowed back into a header chamber 1c as the check valve 4 prevents reverse flow.

[0028] As shown in FIG. 3, the above-mentioned compressed air distribution apparatus is contained in a body 5 of the massaging apparatus along with a control section 8 which is a controller comprised of the compressed air supply source 6, a tank 7 and a pressure sensor 9. The tank 7 storing the compressed air is connected to the supply line connecting the compressed air supply source 6 and the header 1. The distribution port 21b of the respective switching valve 2 is connected to a compressed air access port in the body 5. The air discharged from the discharge port 23b of the respective

switching valve 2, after entering into the body 5, is discharged from a vent hole (not shown) provided at the body 5. The control section 8 is electrically connected to the motor M of the compressed air supply source 6 and the electromagnetic drive section 3 as indicated by a broken line to supply a control signal. Reference numerals 10 shows the massage body having a plurality of air-tight chambers 11.

[0029] FIG. 4 is a circuit diagram schematically showing another embodiment of the pressure control system for the air massage apparatus of the present invention. In this embodiment, a shut-off valve 14 is provided between the header 1 and the switching valve 2 so as to be electromagnetically controlled. And the check valve 4 is provided between the shut-off valve 14 and the switching valve 2.

[0030] By providing the shut-off valve 14 it is possible to selectively control air-tight chambers 11a to 11d of a massage body 10 with the use of a control section 8.

[0031] The function of the pressure control system for air massage according to the present invention will be explained below on the basis of one embodiment of the air pressure type massage apparatus as shown in FIG. 9.

[0032] The massage body 10 is of such a type that the user wears it around the upper limbs or lower limbs and it press-massage these limbs from the hand tips toward the shoulders or from the foot tops toward the thighs in a repeated expand/contract way. As shown in FIG. 9 for example, the user wears it either around one or both of lower limbs.

[0033] The air pressure type massage apparatus is of such a type as to connect the "bundled" side end of air hoses 12, 12 to the above-mentioned massage apparatus body 5 through an adapter 13 for allowing communication to be made between the distribution ports 21b of the respective switching valves 2 and predetermined air-tight chambers 11, 11 and to connect the "separated" side end of the air hoses 12, 12 to predetermined air-tight chambers 11, 11 of the respective massage bodies 10. It is to be noted that, in the case of massaging one leg, it is only necessary to connect the "bundled" side end of the air hoses directly to the massage apparatus body 5.

[0034] The massage is started by fitting the massage bodies 10, 10 around both the legs of the user and, after turning on the power supply of the massage apparatus body 5, turning on a switch on the massage apparatus body 5.

[0035] When the massage is so started, the compressed air supply source 6 is operated to supply compressed air and the control section 8 starts an ON/OFF operation of the electromagnetic drive section 3. The control section 8 performs the operations of the respective electromagnetic drive sections 3 in an ON/OFF fashion in accordance with a previously stored control pattern.

[0036] The ON/OFF control pattern of the electromagnetic drive section 3 is listed below, but the present invention is not limited thereto and it is preferable to store various patterns as the user likes.

[0037] When an explanation is made below about the pattern shown in FIG. 5 for example, a relation of an internal pressure set in the respective air-tight chambers 11a, 11b, 11c, 11d becomes  $11a \geq 11b \geq 11c \geq 11d$ .

[0038] At a time of massaging, an electromagnetic drive section 3 operating the valve body 22 of the switching valve 2 communicating with the air-tight chamber 11a corresponding to the foot top of the user is turned ON and a flow of the compressed air into the air-tight chamber 11a is started. When the pressure in the air-tight chamber 11a reaches a predetermined level, the supply of the compressed air from the compressed air supply source 6 is adjusted so as to retain the pressure in the air-tight chamber 11a below a predetermined level. The pressure adjustment of the compressed air is performed by varying a supply voltage to the compressed air supply source 6 by the control section 8 and adjusting an amount of supply of the compressed air to the massage body 10.

[0039] The pressure in the air-tight chamber 11a is maintained constant because a reverse flow from the supply port 21a into the header chamber 1c is prevented by the check valve 4 provided in a passageway through which the compressed air flows and because the compressed air in the air-tight chamber 11a supplied through the valve body 22 of the switching valve 2 opened by the turning ON of the electromagnetic drive section 3 retains the pressure.

[0040] Then the switching valve 2 of the air-right chamber 11b is opened to start a supply of air into the chamber 11b as in the case of the air-tight chamber 11a. Since the pressure in the air-tight chamber 11a is set to be higher than the pressure in the air-tight chamber 11b, no extra compressed air never flows into the air-tight chamber 11a and hence there is no rise in the pressure in the air-tight chamber 11a.

[0041] Further, since, in the air-tight chamber 11b, a back flow of the compressed air into the header chamber 1c of the header 1 is prevented by the check valve 4, the air-tight chamber 11b is maintained at a set pressure level lower than, or equal to, that of the air-tight chamber 11a. Then, the electromagnetic drive section of the air-tight chamber 11a goes OFF and the air in the air-tight chamber 11a is discharged through the discharge port 23b of the switching valve 2.

[0042] Air flows into the air-tight chamber unit 11c and then into the air-tight chamber 11d, in the same way as into the air-tight chamber units 11a and 11b. Upon lapse of a prescribed time, the electromagnetic drive section 3 associated with the chamber unit 11c is turned off. Similarly, upon lapse of a predetermined time, the electromagnetic drive section 3 associated with the chamber unit 11d is turned off.

[0043] The electromagnetic drive sections 3 are repeatedly turned on and off in the order described above, until a predetermined time elapses from the time the drive section 3 associated with the first air-tight chamber unit 11a is turned on for the first time. The pressures in the air-tight chamber units 11a to 11d are thereby sequentially changed. Hence, the air massage apparatus massages the user, from the toes to the thighs.

[0044] Since, with respect to the voltage control of the compressed air supply source 6, a different internal pressure is set in each air-tight chamber 11, the control of the voltage by the control section 8 is done as will be set out below so as to maintain constant the air pressure generated from the compressed air supply source 6 when compressed air is flowed into the air chamber.

[0045] FIG. 7 is an explanatory view showing the control done by the control section 8 used in the present invention. The control of the compressed air supply source 6 in accordance with the present invention is done by the control section 8. The control section 8 performs the speed control of the drive motor M of the compressor C by a phase control method in a manner shown.

[0046] In FIG. 7,  $\theta$  shows a conduction angle. During the operation of the massage apparatus body 5 except in an discharge period during which the compressed air is discharged from the massage apparatus body 10 through the opening of the discharge port 23b, control is done, by the control of this conduction angle  $\theta$ , so that a sensed pressure by a pressure sensor 9 is maintained to a desired given pressure level.

[0047] Upon the control of the conduction angle  $\theta$ , control is made as set out below so as to suppress any sudden variation of noise (pump noise) produced from the compressed air supply source 6 with a variation of an internal pressure in the respective air-tight chamber 11.

[0048] FIG. 8 shows a difference between a set pressure value and a pressure value measured by the pressure sensor 9 provided at the control section 8. A difference between the measured pressure and the set pressure (hatched area A) is integrated along time. When the integrated value becomes, for example, about  $0.146 \text{ (kgf/cm}^2 \cdot \text{sec)}$ , the conduction angle  $\theta$  is varied.

[0049] When the pressure value measured by the pressure sensor 9 greatly deviates from the set value, it is quickly close changed to the set value by increasing a ratio of varying the conduction angle  $\theta$  in proportion to the difference between the measured pressure and the set pressure.

[0050] It is preferred that the proportion coefficient at the time of varying the conduction angle  $\theta$  be, for example, about  $0.1769 \text{ (deg/(gf/cm}^2))$  in order to raise and lower, for example, the pumping power. The voltage of the compressed air supply source 6 is therefore varied gradually. As a result, the pressure of the air supplied from the source 6 changes little by little. Hence,

the noise of the air being supplied from the source 6 makes does not change so much as to annoy the user of the air massage apparatus.

[0051] The electromagnetic drive sections 3 may be repeatedly turned on and off in such a different manner as is illustrated in FIG. 6. More precisely, the sections 3 for driving, respectively, the valve bodies of the switching valves 2 communicating with the air-tight chamber units 11a to 11d, are sequentially turned on in the order they are mentioned. Each magnetic drive section 3 is stopped upon lapse of a prescribed time from the time it was turned on. The drive sections 3 are repeatedly turned on and off, until a predetermined time elapses from the time the drive section 3 associated with the first air-tight chamber unit 11a is turned on for the first time. The pressures in the air-tight chamber units 11a to 11d are thereby sequentially changed. As a result, the air massage apparatus repeatedly applies a pressure to the user, from the toes to the thighs, and stops applying the pressure at the toes and thighs and the intervening parts at the same time.

[0052] Or a massage pattern is such that, until a predetermined time (not shown) is passed, all the electromagnetic drive sections 3 are simultaneously turned ON and OFF and each part of the user is wholly massaged repeatedly at each given interval in a press-applied/released fashion.

[0053] When the control section 8 turns on the electromagnetic drive section 3, a solenoid coil in the electromagnet casing 33 is energized, inducing an electromagnetic force to retract a movable section 32 into the electromagnetic casing 33 against an urging force of a spring 36. The valve body 22 connected through the operation shaft 31 to the movable section 32 is moved away from the valve seat 21c of the supply port 21a and abuts against the valve seat 23c of the discharge port 23b. Thereby the discharge port 23b is blocked, and the supply port 21a and the distribution port 21b are communicated with each other. The compressed air supplied from the compressed air supply source 6 enters from the outlet port 4a of the check valve 4 connected to the header 1 into the supply port 21a. And it flows from the supply port 21a into the distribution port 21b communicating with the supply port 21a and it further flows from the distribution port 21b past the air hoses 12, 12 and adapter 13 into the predetermined air-tight chambers 11, 11 of the massage bodies 10, 10, thus expanding the associated chambers 11, 11. At this time, the control section 8 connected to the compressed air supply source 6 allows a portion of the compressed air to be discharged to an outside so as to prevent any excessive rise of pressure in the chambers 11a, 11b, ....

[0054] When the control section 8 turns off the electromagnetic drive section 3, a current through the coil is stopped, and the movable section 32 is moved toward the switching valve 2 side under an elastic force of a spring. And the valve body 22 mounted on the distal end

of the operation shaft 31 coupled to the movable section 32 abuts against the valve seat 21c of the supply port 21a to block the supply port 21a and hence a supply of the compressed air from the supply port 21a into the switching valve 2 and, at this time, communication is established between the distribution port 21b and the discharge port 23b to discharge the compressed air in the predetermined air-tight chamber 11 connected to the distribution port 21b through the air hoses 12, 12 and adapter 13 from the respective discharge port 23b and allow the corresponding chamber 11 to be contracted.

[0055] As set out above, after the chambers 11 are expanded and contracted during the set time period with the electromagnetic drive sections 3 rendered ON and OFF, the compressed air supply source 6 is stopped and all the electromagnetic drive sections 3 are turned OFF to cause all the chambers 11 to be contracted, thus finishing a massage action.

[0056] In the alternate embodiment shown in FIG. 4, the switching valves 2 and shut-off valves 14 are connected to the control section 8 by the electric circuit and, since these are separately controlled by the control section 8, the air-tight chambers 11a, 11b, 11c and 11d are further controlled, by adjusting the shut-off valves 14 individually, so that it is possible to arbitrarily adjust individual pressure in each chamber.

[0057] The operation shaft 31 supported on the distal end portion of the movable section 32 is swingable about a fixed pin 35 and somewhat movable in an up/down direction. Even if, therefore, the moving locus of the center of the valve body 22 is not aligned with the centers of the valve seats 21c and 23c of the supply port 21a and discharge port 23b, the center of the valve body 22 and centers of the valve seats 21c and 23c are automatically adjusted and a positive seal is assured there. Further, the valve body 22 is made of an elastic material and ensures a better sealability upon being abutted against the valve seats 21c, 23c, so that it is possible to prevent the leaking of the compressed air.

## Claims

### 1. An air massage system comprising:

- a massage body (10) having a plurality of air-tight chambers (11);
- a compressed air supply source (6, 7) for supplying compressed air to the massage body;
- a compressed air distribution apparatus arranged between the compressed air supply source and the massage body and having a plurality of switching valves (2) communicating the respective air-tight chamber with one of the compressed air supply source and an outer atmosphere;
- a controller (8) for controlling the respective switching valve to expand or contract the

respective chamber, characterized by further comprising

check valves (4) respectively arranged between the compressed air supply source (6, 7) and the switching valves (2) and being open in a direction from the compressed air supply source toward the direction of the switching valve, and the chambers being individually controllable in pressure.

end side of an axial direction thereof and holds the check valve (4) on an other-end side thereof.

2. An air massage system according to claim 1, characterized in that the compressed air supply source (6) has a tank (7) for retaining the compressed air, and the controller (8) has a sensor (9) for detecting a variation of the pressure in the tank and controls an output of the compressed air supply source in accordance with a magnitude of the pressure variation in the tank.
3. An air massage system according to claim 1 or 2, characterized in that the controller (8) supplies the compressed air to the respective air-tight chambers in an air supply sequence while sequentially adjusting a pressure level equal to, or lower than, that of the compressed air.
4. An air massage system according to any one of claims 1 to 3, characterized by further comprising a shut-off valve (14) interruptible between a tank (7) and the check valve (4) and adapted to be controlled by the controller (8).
5. An air massage system according to any one of claims 1 to 4, characterized in that the controller (8) stores a plurality of control patterns each operating the corresponding switching valves (2), any one of these control patterns being selectable from the user.
6. An air massage system according to any one of claims 1 to 5, characterized in that the switching valve (2) comprises: a valve box (21) having a supply port (21a) communicating with the compressed air supply source (6, 7), a distribution port (21b) communicating with the air-tight chambers (11) and an discharge port (23b) communicating with an outer atmosphere; a valve body (22) movably received in the valve box and allowing the distribution port (21b) to communicate with one of the supply port (21a) and discharge port (23b); a solenoid (3) controlled by the controller (8); and a movable member (32) coupled to the valve body (22) and driven by the solenoid.
7. An air massage system according to claim 6, characterized in that the valve box (21) has a substantially cylindrical configuration and has a valve seat (21c) with the supply port (21a) opened on a one-




FIG. 1




FIG. 2






FIG. 3




FIG. 4




FIG. 5




FIG. 6

FIG. 7





FIG. 8




FIG. 9

**This Page Blank (uspto)**

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 018 329 A3

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
19.07.2000 Bulletin 2000/29

(51) Int. Cl.<sup>7</sup>: A61H 23/04

(43) Date of publication A2:  
12.07.2000 Bulletin 2000/28

(21) Application number: 99125665.2

(22) Date of filing: 22.12.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventors:  
• Ishibashi, Shigemitsu  
2-9-4-Nakaikagami Oota-Ku, Tokyo (JP)  
• Nakao, Haruki  
2-9-4, Nakaikagami, Oota-ku, Tokyo (JP)

(30) Priority: 28.12.1998 JP 37404798

(74) Representative:  
Schurack, Eduard F. et al  
Hofstetter, Schurack & Skora  
Balanstrasse 57  
81541 München (DE)

(71) Applicant: Nitto Kohki Co., Ltd.  
Tokyo (JP)

### (54) Air massage system

(57) A compact air massage system which includes massage bodies (10) having a plurality of air-tight chambers (11), a compressed air supply source (6,7) supplying compressed air to the massage body, and a compressed air distribution apparatus arranged between the compressed air supply source and the massage body and having a plurality of switching valves (2) each allowing the respective air-tight chambers to communicate with one of the compressed air supply source and an outer atmosphere. The system further

includes a controller (8) controlling the respective switching valves to allow the respective chambers to be expanded or contracted and check valves (4) each arranged between the compressed air supply source (6,7) and the switching valve (2) and openable from the compressed air supply source toward the direction of the switching valve, by which it is possible to individually adjust pressure in the respective chambers.




FIG. 3

EP 1 018 329 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 12 5665

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	GB 2 285 749 A (HUNTLEIGH TECHNOLOGY PLC) 26 July 1995 (1995-07-26) * page 4, line 4 - page 5, line 33; figure 1 *	1	A61H23/04
X	US 4 374 518 A (VILLANUEVA RAUL) 22 February 1983 (1983-02-22) * column 3, line 17 - column 4, line 66; figures 1,4 *	1,4-6	
A	US 3 826 249 A (LEE A ET AL) 30 July 1974 (1974-07-30) * column 3, line 26 - column 5, line 15 * * column 5, line 45 - column 6, line 14; figures 1,5 *	1,4-6	
A	US 4 029 087 A (DYE JOHN F ET AL) 14 June 1977 (1977-06-14)	1	
P,A, D	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 04, 30 April 1999 (1999-04-30) & JP 11 019145 A (NITTO KOHKI CO LTD), 26 January 1999 (1999-01-26) * abstract *	1-7	TECHNICAL FIELDS SEARCHED (Int.Cl.7) A61H F16K
P,A	EP 0 916 332 A (MEDIC SYSTEMS SOCIETE A RESPON) 19 May 1999 (1999-05-19)	1,2	
A	US 5 261 459 A (ATKINSON GORDON E ET AL) 16 November 1993 (1993-11-16) * abstract *	1	
The present search report has been drawn up for all claims			
Place of search <b>MUNICH</b>		Date of completion of the search <b>9 May 2000</b>	Examiner <b>Georgiou, Z</b>
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 12 5665

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-05-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2285749 A	26-07-1995	NONE	
US 4374518 A	22-02-1983	NONE	
US 3826249 A	30-07-1974	NONE	
US 4029087 A	14-06-1977	CA 1113330 A	01-12-1981
		CA 1085251 A	09-09-1980
		CA 1114704 A	22-12-1981
JP 11019145 A	26-01-1999	NONE	
EP 0916332 A	19-05-1999	FR 2771001 A	21-05-1999
US 5261459 A	16-11-1993	AU 671702 B	05-09-1996
		AU 5669294 A	04-07-1994
		CA 2151135 A	23-06-1994
		EP 0725907 A	14-08-1996
		JP 8506881 T	23-07-1996
		WO 9413987 A	23-06-1994

EPC FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

This Page Blank (uspto)



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

This Page Blank (uspto)